


VCT

 TIS 11 Part 101-2553

450/750 V 70°C FLEXIBLE CONDUCTOR PVC INSULATED AND SHEATHED, ROUND TYPE



CONDUCTOR INSULATION SHEATH

CABLE STRUCTURE

Conductor	: Flexible annealed copper Single-core : Sizes 4 mm ² up to 35 mm ² Multi-cores : Sizes 4 mm ² up to 35 mm ²
Insulation	: Polyvinyl chloride (PVC/D)
Core identification	Single-core : Black 2 Cores : Blue and Brown 3 Cores : Brown, Black and Grey 4 Cores : Blue, Brown, Black and Grey
Sheath	: Black polyvinyl chloride (PVC/ST5)

TECHNICAL DATA

Classification	: Maximum conductor temperature 70°C : Circuit voltage not exceeding 450/750 Volts 450 Volts between Line-to-Earth 750 Volts between Line-to-Line
Testing voltage	: 2,500 Volts
Reference standard	: TIS 11 Part 101-2553, Table 7



APPLICATION


For mobile-electrical equipment used in mines, factories, farm or household appliances. This cable is suitable for use in places where cables come in contact with oils.

Number of core	Nominal cross sectional area (mm ²)	Class of conductor	Insulation thickness nominal (mm)	Sheath thickness nominal (mm)	Overall diameter maximum (mm)	Conductor resistance at 20°C maximum (Ω/km)	Insulation resistance at 70°C minimum (MΩ-km)	Continuous current rating in free air maximum (A)	Cable weight approx. (kg/km)	Standard length (m)
1	4	5	0.9	1.4	8.6	4.95	0.0084	41	90	100/C
	6	5	0.9	1.4	9.4	3.30	0.0071	53	120	100/C
	10	5	1.1	1.8	12.0	1.91	0.0068	74	210	100/C
	16	5	1.1	1.8	13.5	1.21	0.0050	99	270	100/C
	25	5	1.3	2.2	16.0	0.780	0.0048	129	410	100/C
	35	5	1.3	2.2	17.5	0.554	0.0041	160	550	500/D
2	4	5	0.9	1.6	14.5	4.95	0.0084	34	230	100/C
	6	5	0.9	1.6	16.0	3.30	0.0071	44	320	100/C
	10	5	1.1	1.8	20.0	1.91	0.0068	63	500	500/D
	16	5	1.1	2.2	23.0	1.21	0.0050	82	700	500/D
	25	5	1.3	2.4	27.5	0.780	0.0048	108	1,000	500/D
	35	5	1.3	2.6	31.0	0.554	0.0041	133	1,400	500/D

Class of conductor 5 : Flexible

C : Packing in coil
D : Packing in drum

VCT		 TIS 11 Part 101-2553			
450/750 V 70°C FLEXIBLE CONDUCTOR PVC INSULATED AND SHEATHED, ROUND TYPE					
					
CONDUCTOR		INSULATION		SHEATH	
CABLE STRUCTURE			TECHNICAL DATA		
Conductor	: Flexible annealed copper : Single-core : Sizes 4 mm ² up to 35 mm ² : Multi-cores : Sizes 4 mm ² up to 35 mm ²		Classification	: Maximum conductor temperature 70°C : Circuit voltage not exceeding 450/750 Volts 450 Volts between Line-to-Earth 750 Volts between Line-to-Line	
Insulation	: Polyvinyl chloride (PVC/D)		Testing voltage	: 2,500 Volts	
Core Identification	: Single-core : Black : 2 Cores : Blue and Brown : 3 Cores : Brown, Black and Grey : 4 Cores : Blue, Brown, Black and Grey		Reference standard	: TIS 11 Part 101-2553, Table 7	
Sheath	: Black polyvinyl chloride (PVC/ST5)		APPLICATION		
			For mobile-electrical equipment used in mines, factories, farm or household appliances. This cable is suitable for use in places where cables come in contact with oils.		
Number of core	Nominal cross sectional area (mm ²)	A.C. Resistance	Inductance	Reactance	Impedance
		R (Ω/km)	L (mH/km)	XL (Ω/km)	Z (Ω/km)
1	4	5.9200	0.58267	0.18305	5.9228
	6	3.9500	0.54956	0.17265	3.9538
	10	2.2900	0.54230	0.17037	2.2963
	16	1.4500	0.52085	0.16363	1.4592
	25	0.9334	0.51783	0.16268	0.9475
2	35	0.6630	0.49968	0.15698	0.6813
	4	5.9200	0.29835	0.08373	5.9207
	6	3.9500	0.27741	0.08715	3.9510
	10	2.2900	0.29736	0.08474	2.4418
	16	1.4520	0.25745	0.08088	1.4543
	25	0.9369	0.25468	0.08001	0.9403
	35	0.6877	0.24497	0.07696	0.6721

VCT										
TIS 11 Part 101-2553										
450/750 V 70°C FLEXIBLE CONDUCTOR PVC INSULATED AND SHEATHED, ROUND TYPE										
										
			CONDUCTOR	INSULATION	SHEATH					
CABLE STRUCTURE						TECHNICAL DATA				
Conductor : Flexible annealed copper Single-core : Sizes 4 mm ² up to 35 mm ² Multi-cores : Sizes 4 mm ² up to 35 mm ² : Polyvinyl chloride (PVC/D)						Classification : Maximum conductor temperature 70°C : Circuit voltage not exceeding 450/750 Volts 450 Volts between Line-to-Earth 750 Volts between Line to Line				
Insulation Core Identification Single-core : Black 2 Cores : Blue and Brown 3 Cores : Brown, Black and Grey 4 Cores : Blue, Brown, Black and Grey						Testing voltage : 2,500 Volts Reference standard : TIS 11 Part 101-2553, Table 7				
Sheath : Black polyvinyl chloride (PVC/ST5)						APPLICATION For mobile-electrical equipment used in mines, factories, farm or household appliances. This cable is suitable for use in places where cables come in contact with oils.				
Number of core	Nominal cross sectional area (mm ²)	Class of conductor	Insulation thickness nominal (mm)	Sheath thickness nominal (mm)	Overall diameter maximum (mm)	Conductor resistance at 20°C maximum (Ω/km)	Insulation resistance at 70°C minimum (MΩ-km)	Continuous current rating in free air maximum (A)	Cable weight approx. (kg/km)	Standard length (m)
3	4	5	0.9	1.6	15.5	4.95	0.0084	29	280	100/C
	6	5	0.9	1.8	17.5	3.30	0.0071	38	390	100/C
	10	5	1.1	2.0	21.5	1.91	0.0068	53	650	500/D
	16	5	1.1	2.4	25.0	1.21	0.0050	71	900	500/D
	25	5	1.3	2.6	30.0	0.780	0.0048	94	1,300	500/D
	35	5	1.3	2.8	33.5	0.554	0.0041	116	1,700	500/D
4	4	5	0.9	1.8	17.0	4.95	0.0084	29	350	100/C
	6	5	0.9	2.0	19.5	3.30	0.0071	38	490	100/C
	10	5	1.1	2.2	24.0	1.91	0.0068	53	800	500/D
	16	5	1.1	2.6	28.0	1.21	0.0050	71	1,100	500/D
	25	5	1.3	2.8	33.0	0.780	0.0048	94	1,700	500/D
	35	5	1.3	3.1	37.0	0.554	0.0041	116	2,200	500/D

Class of conductor 5 : Flexible

 C : Packing in coil
 D : Packing in drum

VCT

 TIS 11 Part 101-2553

450/750 V 70°C FLEXIBLE CONDUCTOR PVC INSULATED AND SHEATHED, ROUND TYPE



CABLE STRUCTURE		TECHNICAL DATA			
Conductor	: Flexible annealed copper Single-c : Sizes 4 mm ² up to 35 mm ² Multi-cor: Sizes 4 mm ² up to 35 mm ²	Classification	: Maximum conductor temperature 70°C : Circuit voltage not exceeding 450/750 Volts 450 Volts between Line-to-Earth 750 Volts between Line-to-Line		
Insulation	: Polyvinyl chloride (PVC/D)	Testing voltage	: 2,500 Volts		
Core Identification	Single-co : Black 2 Cores : Blue and Brown 3 Cores : Brown, Black and Grey 4 Cores : Blue, Brown, Black and Grey	Reference standard	: TIS 11 Part 101-2553, Table 7		
Sheath	: Black polyvinyl chloride (PVC/ST5)	APPLICATION			
For mobile-electrical equipment used in mines, factories, farm or household appliances. This cable is suitable for use in places where cables come in contact with oils.					
Number of core	Nominal cross sectional area (mm ²)	A.C. Resistance	Inductance	Reactance	Impedance
		R (Ω/km)	L (mH/km)	XL (Ω/km)	Z (Ω/km)
3	4	5.9200	0.29835	0.09373	5.9207
	6	3.9500	0.27741	0.08715	3.9510
	10	2.2900	0.26977	0.08475	2.2918
	16	1.4500	0.25745	0.08088	1.4523
	25	0.9335	0.25468	0.08001	0.9369
35	0.6632	0.24497	0.07696	0.6677	
4	4	5.9200	0.34495	0.10837	5.9210
	6	3.9500	0.32410	0.10182	3.9513
	10	2.2900	0.31624	0.09935	2.2922
	16	1.4500	0.30417	0.09556	1.7366
	25	0.9335	0.30171	0.09469	0.9383
35	0.6631	0.29062	0.09130	0.6694	